



THESE DRAWINGS ARE NOT TO BE USED FOR CONSTRUCTION DRAWINGS.

ALL WORK SHALL CONFORM TO APPLICABLE REQUIREMENTS OF LOCAL, STATE, AND FEDERAL AGENCIES HAVING JURISDICTION. AIASSA DESIGNERS ASSUMES NO RESPONSIBILITY FOR THE SUPERVISION NOR PROPER EXECUTION FOR THE WORK SHOWN ON THESE DRAWINGS, NOR FOR ANY EXISTING CONSTRUCTION. ANY REPRODUCTION IN ANY FORM OR PART THEREOF, IS STRICTLY PROHIBITED WITHOUT THE WRITTEN CONSENT OF AIASSA DESIGNERS.

Project: F-2

Sheet: F-2

Revision/Issue:

--	--

Date:

Designer Name and Address:
 DENNIE AIASSA 2800 ROAD #151
 SAN JOSE, CA 95131
 (408) 230-2989
 WWW.AIASSADESIGNERS.COM

WINDOW SCHEDULE (0)

(R)REMOVING (N)EW (E)XISTING	MARK	SIZE	WIDTH	HEIGHT	STYLE
R	1	3'-3"	3'-1"	SLIDER	
R	2	3'-6"	3'-4"	SLIDER	
R	3	5'-11"	3'-2"	GRANK	
N	4	1'-0"	6'-8"	SECURITY GLASS SAFETY GLAZING	
N	5	4'-0"	3'-0"	SLIDER	
N	6	2'x4'x2'	4'-0"	BAY/FREE FAB	
N	7	5'-0"	2'-11"	SLIDER	
E	8	5'-8"	2'-11"	SLIDER	
E	9	5'-6"	2'-10"	SLIDER	
E	10	2'-7"	2'-6"	SLIDER	
E	11	2'-7"	4'-6"	SLIDER	
E	12	9'-7"	4'-6"	SLIDER	
E	13	2'-7"	4'-6"	SLIDER	
E	14	4'-6"	4'-6"	SLIDER	
E	15	7'-5"	3'-7"	OPENING	
E	16	5'-8"	3'-10"	SLIDER	

NOTE: ALL HEADERS TO BE 4 X 12.

DOOR SCHEDULE (000)

(R)REMOVING (N)EW (E)XISTING	MARK	DOOR SIZE	WIDTH	HGT	STYLE
R	001	3'-0"	6'-8"		
R	002	1'-8"	6'-8"		
R	003	2'-8"	6'-8"		
E	004	15'-0"	6'-10"		ROLL UP
N	005	3'-0"	6'-8"		(E) WITH SIDE LIGHT
N	006	2'-4"	6'-8"		1 3/8" SOLID WOOD, TIGHT FITTING, SELF-CLOSING OR 20 MINUTE FIRE PROOF
N	007	3'-0"	6'-8"		ARCH OPENING
N	008	2'-4"	6'-8"		
N	009	2'-8"	6'-8"		
N	010	2'-4"	6'-8"		
N	011	2'-8"	6'-8"		
N	012	5'-0"	6'-8"		MIRROR SLIDER
N	013	2'-8"	6'-8"		
N	014	2'-8"	6'-8"		
N	015	2'-8"	6'-8"		
E	016	4'-11"	8'-0"		SLIDER
E	017	4'-11"	8'-0"		SLIDER
E	018	2'-8"	6'-8"		
E	019	4'-11"	8'-0"		SLIDER
E	020	2'-8"	6'-8"		
E	021	2'-4"	6'-8"		
E	022	1'-8"	6'-8"		HALL ENTRY
E	023	2'-8"	6'-8"		POCKET
E	024	2'-8"	6'-8"		
E	025	1'-9"	6'-8"		DOOR OPENING
E	026	8'-0"	6'-8"		(E)SLIDER
E	027	6'-0"	6'-8"		(E)SLIDER
E	028	2'-4"	6'-8"		(E)

NOTE: ALL HEADERS TO BE 4 X 12.

CEILING/FLOOR ACCESS (000)

(R)REMOVING (N)EW (E)XISTING	MARK	DOOR SIZE	WIDTH	LT	ACCESS
E	001	1'-11"	1'-11"		ROOF
N	002	2'-0"	3'-0"		STORAGE
N	003	1'-6"	2'-0"		FLOOR
N	004	2'-0"	3'-0"		STORAGE

F-2.2 DOOR AND WINDOW SCHEDULE

NOTE: Provide one-hour fire resistive assembly at all exterior walls. (FMC 7-1221, Item 3601.31)

SHEAR WALL SCHEDULE			
TYPE	SHEATHING	EDGE NAILING	FIELD NAILING
△	3/8" OSB	10d@4"	10d@24"

F-2.3 SHEAR WALLS SCHEDULE

ROOM REQUIREMENT NOTES:

1. AT BATHROOM AND LAUNDRY ROOMS, PROVIDE OPENING WINDOW AREA WITH 5% OF FLOOR AREA (1.5 SQ FT MINIMUM) OR MECHANICAL VENTILATION (5 AIR CHANGES PER HOUR). THE POINT OF DISCHARGE OF EXHAUST AIR SHALL BE AT LEAST THREE FEET FROM ANY OPENING INTO THE BUILDING. THE EXHAUST VENTS SHALL BE EQUIPPED WITH BACKDRAFT DAMPER TO COMPLY WITH ENERGY REGULATIONS. (UBC 1203.3)
2. GLAZING ADJACENT TO DOORS AND GLAZING IN FIXED PANELS ADJACENT TO A WALKING SURFACE MUST BE OF SAFETY GLAZING MATERIALS, E.G. WINDOW AT #4 (FRONT DOOR). (CBC 2406.1)
3. PROVIDE SECURITY GLASS AT LIGHT PANELS NEXT TO MAIN ENTRY DOOR (FMC ORDINANCE 2141, SECTION 7-1222, ITEM 1007)

PLUMBING AND MECHANICAL REQUIREMENT NOTES:

1. BATHROOM FLOOR AND WALL TILE MATCHING 12 X 12 CERAMIC TILES. 1/2" HARDYBACKER TO BE APPLIED BEFORE THE TILE. (C.O.F. MEMO 7/20/90). TILE TO EXTEND UP WALL TO BE 6" TALL.
2. PROVIDE ULTRA LOW FLUSH TOILET (1.6 GALLONS/FLUSH) AT ALL NEW BATHROOMS. ASSEMBLY BILL #2355
3. PROVIDE PROTECTION BARRIER IN FRONT OF ANY GAS APPLIANCE LOCATED AT GARAGE IN THE NORMAL PATH OF VEHICLES. (UPC510.3, UMC 308) THIS SHOULD BE IN FRONT OF ANY WATER HEATER.
4. BATH TUB/SHOWER TO HAVE SLIDING SHOWER GLASS DOORS.
5. BATH TUB AND SHOWER INCLOSURE TO BE INSTALLED IN MASTER BATH.

BUILDING REQUIREMENT NOTES:

1. PROVIDE UNDER FLOOR VENTILATION OF NOT LESS THAN 1 SQ FT FOR EACH 150 SQ FT OF UNDER-FLOOR AREA.(UBC 2306.7)
2. PROVIDE UNDERFLOOR ACCESS SIZE AND LOCATION (18" X 24"MIN.) (UBC 2306.7)
3. PROVIDE ATTIC ACCESS OPENING SIZE (22" X 30" MINIMUM)

